


WEIGHT CLASS
10.4 TONNE
| TB295W |
2-PIECE BOOM



STAGE V
READY



WHEELED EXCAVATOR

takeuchi
From World First to World Leader

New TB295W wheeled excavator road ready & Stage V compliant

The latest Stage V ready TB295W is Takeuchi's new high-performance wheeled excavator, packed full of on-road features. A powerful 4 dual-wheel drive machine, the new TB295W is designed and built for motorway, road and streetworks applications with out-rigger options for added stability.

The TB295W features a new versatile 2-piece boom with twin boom rams, increasing performance, functionality and improving on-site manoeuvrability. The maximum dump height of 6480mm and the positioning of the additional lifting cylinders reduces the risk of damage when truck loading.

With increased dig depth of 4115mm and greater ground reach to 7555mm the TB295W provides heavy duty on-site performance and weighs in at 10,377 (10,667kg with outriggers).

A very flexible on-road vehicle built for maximum excavator performance.

Complete with a 85kW Deutz turbo engine;

Stage V • Low Emission • Low Noise.

Power performance combined with maximum breakout force all compliant with low emission zone regulations.

STAGE V 
READY



COMPATIBLE BREAKER

The TB295W is compatible with a Takeuchi TKB402-S & TKB802-S sound suppressed hydraulic breaker. Designed to meet the requirement for quieter operating environments.





OPERATOR COMFORT

A large enclosed ROPS/FOPS cab with digital air-con climate control as standard, along with retractable front window, wiper, rainguard and sunshade.

The styled interior features intuitive controls, ample space, improved comfort and visibility.

The 10-way adjustable high back heated air suspension seat provides for the operator's optimal position for all day driving and excavating. Radio MW-FM/MP3/USB/ Bluetooth with Stereo Speakers and 12V/24V power outlet.



NEW LED LIGHTING

Improved visibility in the dullest winter conditions with powerful workzone LED lighting.



HEAVY DUTY BUILD - POWERFUL

Powered by a very fuel-efficient Stage V turbo Deutz Engine, combined with AdBlue.

The turbocharged diesel engine with auto idle and a dial throttle control provide fuel saving economy.

The heavy-duty boom and arm are robust for tough breaking out.

Takeuchi's TB295W is a proven powerful wheeled excavator ideal for streetworks / on-road excavating.

For plant hire and groundworks contractors, a wheeled option is essential for road applications and the new TB295W offers a powerful addition to the fleet.

The 2-piece boom arrangement offers versatility to reduce working height, ideal in confined working zones.

Retracting the boom (moving the load centre closer to the excavator) enhances lift performance, out-lifting a mono boom when up close to the machine.

The enhanced working range and lifting capabilities of the new 2-piece boom configuration allow the operator to navigate site utilities easier, lift loads safer and operate attachments in a more versatile way.

With a reputation for reliability, Japanese build quality makes all the difference.

MAXIMUM OPERATING PERFORMANCE



With a machine footprint of just 2335 x 3745mm, the new TB295W has a relatively compact size to get maximum accessibility on restricted streetwork sites.

Takeuchi joystick controls and conveniently located switch arrangement give finger-tip precision control with smooth hydraulics. Fitted with cushioned main boom, arm and swing cylinders and hose burst check valves, to maintain load control in the event of a hose failure. Adjustable auxiliary flow and password protected settings with multiple attachment presets all accessible from operator seat.

The selectable lift alarm provides an audible warning when the boom is reaching maximum hydraulic lifting capacity. The TB295W has factory fitted hydraulic hitch steel pipework as standard.

MAINTENANCE FEATURES



The TB295W is designed for maximum service access right round the cab.

The new Stage V engine now comes with DPF and SCR emission after-treatment


Ground level easy access points for the battery and regular service points.



The machine comes with a large well positioned toolbox under the cab, supplied with a tool kit and grease gun.

Electric refuelling pump with extended length for easy fuelling.

Reliable well protected hydraulic hoses help reduce maintenance costs.



- Electronic engine monitoring system
- Self bleeding fuel system - high capacity fuel filters
- TFM - remote engine monitoring system
- New radiator coolant sight gauge
- Service interval - 500 hours



ON - SITE FEATURES



Wide-angle colour rear-view camera, with auto-reverse activation.

The rear fisheye mirror, LED workzone lighting and roof beacon socket all provide maximum on-site safety.

A larger than average parallel lift dozer blade as standard.

INDEPENDENT OUT RIGGERS are a factory fitted option. Easy to position to provide the added stability that might be required on gradients and un-even terrain.





ROAD FEATURES

TB295W is a road legal vehicle when registered and taxed.

A highly flexible on-road excavator, with heavy duty twin wheels, industrial 14 ply tyres, rugged axles and undercarriage provide maximum strength in all terrains.

DRIVING

The TB295W is an easy to drive wheeled option with all the typical on-road features, an adjustable steering column both height and rake, provides for all sizes of operators to give a comfortable drive.

Selectable hand or foot engine speed controls and fully supported travel pedal, footrests and offset foot pedal.

TRAVEL SPEED

With up to 30kph travel speed and auto cruise facility, the TB295W is ideal for on-road highways and street works applications.

SAFETY

Hi visibility well positioned road and LED workzone lights alongside blind-spot mirrors make for the safest possible drive. The added height of TB295W gives excellent all-round operator visibility on-road and on-site with in-built reversing camera as standard. Heavy duty anti-slip steps and prop-shaft guard for added on-site protection.

BRAKES

Highly efficient oil immersed hydraulic brakes with locking foot brake pedal, switch activated parking brake and selectable switch from manual to auto axle lock when digging.


AXLE & UNDERCARRIAGE

The undercarriage and axles are built for the rigours of road and site with rigid strength and switch activated diff lock for added traction. The undercarriage has universal out rigger and blade mounting points at both ends of the machine and onboard anti-roll wheel chocs.



NEW LCD FULL COLOUR DISPLAY

Provides easy to see functionality. The colour VDU gives excellent operator control illuminating all machine functions and warning alerts. The split screen displays both the operating functions and the wide angle, colour rear-view camera, with auto reverse activation.



TFM - TAKEUCHI FLEET MANAGEMENT


Takeuchi Fleet Management is designed to help you better manage your fleet and lower your overall operating costs.



PROTECT YOUR INVESTMENT

The TB295W comes with the **TSS Takeuchi Security System** as standard.





**2 YEAR
2,000 HOUR
WARRANTY***

Takeuchi machines come with a 2 year/2000 hours warranty as standard. Warranty exceptions to 1 year: fuel injection systems, electrical components, paint work and *emission control items. (*applicable models).

Before fitment of a hydraulic attachment, machine auxiliary pressure and flow should be accurately measured.

*Lifting; the mass weight of slings / hitches / bucket to be deducted from the rated load to determine the net load that may be lifted.

TB295W Stage

Standard UK Specification 2-piece Boom

Engine	
Make	DEUTZ
Model	TCD3 6L4
Rated Output (kW)/rpm/HP	85 / 2200 / 113.9
Cylinders	4
Displacement (cc)	3621
Electrical System	24V 90A x2

Dimensions & Weight

Weight 2 piece with blade / with outrigger incl fuel, hitch, bucket (kg)	10377 / 10667
Overall Length (mm)	6565
Overall Length on road (mm)	5020
Width (mm)	2335
Height (mm)	3010
Ground Clearance (mm)	320

Operating Information

Max Digging Depth (mm)	4115
Max Dump Height (mm)	6480
Max Reach at Ground Level (mm)	7555
Max Vertical Digging Depth (mm)	3645
Bucket Digging Force (kN)	58.9
Long Arm Digging Force (kN)	39.7
2-piece boom Max Lift	
Full Reach daN*	1372 / 723 / 1013
2-piece boom Max Lift daN*	3773 / 2540 / 3390

Hydraulic System

Set Pressure (bar)	275
Pump Type	Variable piston x 2 + gear pump X 3
1st Auxiliary Maximum Flow (l/min) / Pressure (bar)	120 / 200
*2nd Auxiliary Maximum Flow (l/min) / Pressure (bar)	46 / 200

Swing System

Boom Swing Angle (R/L)	60° / 70°
Slew Speed (rpm)	10.1
Slew Motor	Constant Vol Piston
Slew Brake	Wet Friction Plate

Undercarriage

Tyre Size	8.25 - 20 - 14PR
Drive Line	All Wheel Drive
Travel Brake	Disc & Brake Lock
Steering	Front Setting System
Wheelbase	2200
Tyre Pressure (psi)	95
Travel Speed - 2 speeds (km/h)	30
Maximum Gradeability	35°

Capacities

Hydraulic System (l)	200
Fuel Tank (l)	162
AdBLUE (l)	10
Engine Lubrication (l)	10

In accordance with our established policy of constant improvement, we reserve the right to amend these specifications at any time without notice. Photographs shown may feature non-standard equipment.

07/2021

For more information locally contact:

Takeuchi Mfg (UK) Ltd, Unit E2B Kingsway Business Park,
John Boyd Dunlop Drive, Rochdale, Lancashire OL16 4NG
Tel: 01706 657 722 Email: info@takeuchi-mfg.co.uk
www.takeuchi-mfg.co.uk



TAKEUCHI
From World First to World Leader